


HSK-M-EX Cablegland



Description

Metal cable gland with improved diaphragm closure system with NBR seal and an IP68 protection rating (10 bar) according to EN 60529. Available in metric threads from M12 to M63 and in PG7 to PG48 threads for various cable diameters. Made of nickel-plated brass. For ATEX applications with explosive atmospheres.

Advantages

Made of nickel-plated brass.

ATEX Classification: II 2G 1D.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C. Protection index EN 60529: IP68 with 10 bar pressure for water immersion.

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in ATEX classified installations with risk of fire or explosion, industrial, OEM equipment manufacturing, outdoor, industrial and marine applications.

Solutions



OFFSHORE, PORTS



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics				
 LTN	 M12, M16, M20, M25, M32, M40, M50, M63	 LATÓN NIQUELADO,NBR,POLIAMIDA	 IP68	 -15 / 90 °C
		6		
		ETIM 10		
 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA		EC000441		

Product data									
				L _{mm}		Ref	kg/u		
M12	6.5	3 / 6.5	9	25.5	14	22081120	0,020	50	
M16	6	4 / 8	11	27	17	22081160	0,020	50	
M16	6	6 / 10	14	28	20	22081161	0,020	50	
M20	6	6 / 12	16	29	22	22081200	0,030	50	
M20	6	10 / 14	18	30	24	22081201	0,030	50	
M25	7	14 / 18	22	33	30	22081250	0,050	25	
M32	8	20 / 25	30	39	40	22081320	0,100	25	
M40	8	22 / 32	39	45	50	22081400	0,171	10	
M50	9	32 / 38	48	46	57	22081500	0,222	5	
M63	10	37 / 44	51	48	64	22081630	0,295	5	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic