


Fixing Clip



Description

Polyamide 6 fixing clip in grey color (RAL 7035) for rigid and rigid and flexible halogen free and PVC conduits. Accessory for mounting conduits with fixing by pressure. Available in different sizes.

Advantages

It has a lateral connection system with another clip that allows for the parallel assembly of the conduits.

Quick assembly by means of pressure.

Suitable for the fixing of rigid and corrugated conduits.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Applications

Suitable for fixing RLH, CLH, RPVC and CPVC rigid and corrugated conduits for the protection of electric cables in building, tertiary and industrial applications.

Solutions



Fixing Clip

Main technical characteristics

Colour Grey RAL 7035	DN NW16, NW20, NW25, NW32, NW40, NW50	M Polyamide 6	°C -15 / 90
LIBRE DE HALÓGENOS, NO PROPAGADOR DE LA LLAMA		ETIM 10 EC000368	

Product data

DN	L _(mm)	Ref	kg/u	Q ₀
NW16	22	55023016	0,004	100
NW20	28	55023020	0,004	100
NW25	33	55023025	0,005	100
NW32	41	55023032	0,006	80
NW40	52	55023040	0,016	30
NW50	64	55023050	0,020	20

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

