

CLH Coupler

1/2



Description

Grey polypropylene coupler (RAL 7035) with an IP44 protection rating for CLH flexible conduits. Accessory for mounting flexible conduits to junction boxes.

Advantages

Supplied complete with nut.

Protection index EN 60529: IP44.

For connection of CLH corrugated conduits to boxes.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made from polypropylene, halogen free.

Applications

Suitable for halogen-free corrugated conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

CLH Coupler

Main technical characteristics

 Colour	Grey RAL 7035	 DN	NW16, NW20, NW25	 M16, M20, M25	 50	 Polypropylene	 IP44	 -15 / 90 °C
 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA			ETIM 10 EC000939					

Product data

DN		Ref	kg/u
NW16	M16	55007116	0,005
NW20	M20	55007120	0,007
NW25	M25	55007125	0,012

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

