

Adjustable riser Pemsa Vulcan



Description

Advantages

Applications

Solutions



Adjustable riser Pemsa Vulcan

Main technical characteristics

PG3, Pregalvanised, ZM High Resistance Alloy	12, 18, 25, 50	50, 75, 100, 150, 225, 300, 450, 600, 750, 900	1
Steel with surface coating	20 J	IP44	-50 / 150 °C
		A1 No combustible	ETIM 10

Product data

§	®	Class IEC 61537	12	18	Ref	kg/lr
PG	PG3, Pregalvanised	Class 3	12	50	82004888	0,214
PG	PG3, Pregalvanised	Class 3	12	75	82004889	0,300
PG	PG3, Pregalvanised	Class 3	12	100	82004890	0,383
PG	PG3, Pregalvanised	Class 3	12	150	82004891	0,549
PG	PG3, Pregalvanised	Class 3	12	225	82004892	0,797
PG	PG3, Pregalvanised	Class 3	18	300	82004893	1,632
PG	PG3, Pregalvanised	Class 3	25	50	82004894	0,302
PG	PG3, Pregalvanised	Class 3	25	75	82004895	0,388
PG	PG3, Pregalvanised	Class 3	25	100	82004896	0,471
PG	PG3, Pregalvanised	Class 3	25	150	82004897	0,637
PG	PG3, Pregalvanised	Class 3	25	225	82004898	0,885
PG	PG3, Pregalvanised	Class 3	25	300	82004899	1,705
PG	PG3, Pregalvanised	Class 3	25	450	82004900	2,453
PG	PG3, Pregalvanised	Class 3	25	600	82004901	3,209
PG	PG3, Pregalvanised	Class 3	50	50	82004902	0,433
PG	PG3, Pregalvanised	Class 3	50	75	82004903	0,519
PG	PG3, Pregalvanised	Class 3	50	100	82004904	0,602
PG	PG3, Pregalvanised	Class 3	50	150	82004905	0,769
PG	PG3, Pregalvanised	Class 3	50	225	82004906	1,518
PG	PG3, Pregalvanised	Class 3	50	300	82004907	1,903
PG	PG3, Pregalvanised	Class 3	50	450	82004908	2,650
PG	PG3, Pregalvanised	Class 3	50	600	82004909	3,406
PG	PG3, Pregalvanised	Class 3	50	750	82004910	6,790
PG	PG3, Pregalvanised	Class 3	50	900	82004911	8,055
PG	PG3, Pregalvanised	Class 3	25	750	82004912	6,533
PG	PG3, Pregalvanised	Class 3	25	900	82004913	7,798
AZ+	ZM High Resistance Alloy	Class 8	25	750	82004914	6,533
AZ+	ZM High Resistance Alloy	Class 8	25	900	82004915	7,798
AZ+	ZM High Resistance Alloy	Class 8	25	50	82004916	0,302
AZ+	ZM High Resistance Alloy	Class 8	25	75	82004917	0,388
AZ+	ZM High Resistance Alloy	Class 8	25	100	82004918	0,471
AZ+	ZM High Resistance Alloy	Class 8	25	150	82004919	0,637
AZ+	ZM High Resistance Alloy	Class 8	25	225	82004920	0,885
AZ+	ZM High Resistance Alloy	Class 8	25	300	82004921	1,705
AZ+	ZM High Resistance Alloy	Class 8	25	450	82004922	2,453



§	Ⓕ	Ⓖ 61537	Ⓜ	Ⓜ	Ref	kg/u
AZ+	ZM High Resistance Alloy	Class 8	25	600	82004923	3,209
AZ+	ZM High Resistance Alloy	Class 8	50	50	82004924	0,433
AZ+	ZM High Resistance Alloy	Class 8	50	75	82004925	0,519
AZ+	ZM High Resistance Alloy	Class 8	50	100	82004926	0,602
AZ+	ZM High Resistance Alloy	Class 8	50	150	82004927	0,769
AZ+	ZM High Resistance Alloy	Class 8	50	225	82004928	1,518
AZ+	ZM High Resistance Alloy	Class 8	50	300	82004929	1,903
AZ+	ZM High Resistance Alloy	Class 8	50	450	82004930	2,650
AZ+	ZM High Resistance Alloy	Class 8	50	600	82004931	3,406
AZ+	ZM High Resistance Alloy	Class 8	50	750	82004980	6,790
AZ+	ZM High Resistance Alloy	Class 8	50	900	82004981	8,055

§ Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic