

Adjustable riser Pemsa Vulcan (Ref: 82004916)



Description

Advantages

Applications

Solutions



Adjustable riser Pemsa Vulcan (Ref: 82004916)

Product data			
ETIM 10		u	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		1	
Protection System		Material	
AZ+		Steel with surface coating	
Finish		Impact Strength (J)	
ZM High Resistance Alloy		20 J	
Resistance Class		IP	
Class 8		IP44	
Flange (mm)		Working temperature range (°C)	
25		-50 / 150 °C	
Width (mm)		Fire resistance	
50		A1 No combustible	
kg/u			
0,302			

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass
Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

