



**Megaband CPS 30° Inside Riser** ( Ref: 82002299 )

1/2



### Description

Metal accessory for creating a 30° inside riser in the wiring installation with the Megaband® CPS ladder. Of 100 mm height, Width 200 mm, Angle of 30 °, With AL protection system. It allows descents and height changes to be made with great ease. Radius of curve 200 and 600. Made from Aluminium alloy 6063T6.

### Advantages

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Available in 100 mm height and 200, 300, 400 and 600 mm wide.

Made of Aluminum alloy 6063T6. Excellent corrosion resistance.

Only the Megaband® M8 joint kit or M8 nuts and bolts required

Its design allows to make drops and changes of angle at 30° with great ease

### Applications

Suitable for cable conduit installations in the Oil & Gas and Petrochemical Industry, Offshore Platforms, Ports and Maritime Applications in general. Industrial projects in aggressive environments and with high corrosion on the coast and seashore, Power Plants and Renewable Energy.

### Solutions



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



| Product data                          |  |                                |                   |
|---------------------------------------|--|--------------------------------|-------------------|
| ETIM 10                               |  | EC001535                       |                   |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |  |                                |                   |
| Protection System                     |  | AL                             |                   |
| Finish                                |  | 6063T6 Aluminium               |                   |
| Flange (mm)                           |  | 100                            |                   |
| Width (mm)                            |  | 200                            |                   |
| R (mm)                                |  | 800                            |                   |
| Angle                                 |  | 30                             |                   |
|                                       |  | kg/u                           | 4,050             |
|                                       |  | u                              | 1                 |
|                                       |  | Material                       | Aluminum          |
|                                       |  | Impact Strength (J)            | 20 J              |
|                                       |  | Working temperature range (°C) | -50 / 150 °C      |
|                                       |  | Fire resistance                | A1 No combustible |

| Protection System                 |
|-----------------------------------|
| CU - Copper electroplated         |
| PG - Pregalvanised                |
| EZ - Electrogalvanised            |
| BC - Electrogalvanised Bichromate |
| BK8 - High Resistance Coating     |
| GC - Hot Dip Galvanising          |
| INOX - Stainless Steel            |
| PT - Polyester Paint              |
| AL - Aluminum                     |
| LN - Brass or Nickel-plated brass |

| Insulating materials                      |
|-------------------------------------------|
| PC+ABS - Halogen Free Polycarbonate + ABS |
| PVC - Polyvinyl Chloride                  |
| PP - Halogen Free Polypropylene           |
| PA6 - Halogen Free Polyamide 6            |
| PA12 - Halogen Free Polyamide 12          |
| PU - Polyurethane                         |
| PE - Polyethylene                         |
| NBR - NBR rubber                          |
| PET - Thermoplastic Polyester             |
| TPV - Thermoplastic                       |