



Description

Insulating inside rise of 90° for the management of cable for Metatray® cables trays and trunkings. Of 60 mm height, Width 100 mm. Manufactured in PVC-based Thermoplastic insulating material. Of 60 mm height, Width 150 mm. Grey RAL 7035 colour for the support, protection and conduction of cables.

Advantages

Excellent performance in corrosive environments, weather and exposure to UV radiation.

Protection grade IP4X or IP44 and Impact Grade 20 J (EN 61537) and IK10 (EN50085)

Insulating material, electrical safety and reduced maintenance costs.

Aenor N mark on product standards EN 61537 and EN 50085. CE compliance with directive 2014/35/EU.

Non-flame-propagating. Reaction to fire, V0 grade and M1 classification

Applications

Solutions



Product data

ETIM 10	EC002400	Material	PVC
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0,003	Working temperature range (°C)	-20 / 60 °C
Colour	Grey RAL 7035	Fire resistance	GRADO UL94: V0
Flange (mm)	60	UV Behaviour	Resistant acc. to UL568
Width (mm)	150		
kg/u	1,011		
u	1		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications



