

Megaband REP 90° Outside Riser



Description

Metal accessory for creating an outside riser in the wiring installation with the Megaband® REP ladder. It allows ascents and height changes to be made at a 90° angle with great ease. Assembly using bolts. Made from steel with GC Protection system.

Advantages

Its conical tip allows more contact with the element to which it is screwed.

Available in heights 70, 100 120 mm and widths 100 to 600 mm.

Specially designed for the petrochemical sector, with REPSOL approvals, ED-P-11-02

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

Suitable for creating level changes in the distribution of cables on Megaband® REP trays in electrical and telecommunications installations and supporting large loads in industrial, petrochemical, Oil & Gas, power plants, mining and cement installations.

Solutions



Main technical characteristics									
 GC	 Class 8	 70, 100, 120	 100, 200, 300, 400, 600	 300	90	 1	 Steel with surface coating		
 20 J	 -50 / 150 °C	 A1 No combustible	ETIM 10 EC001535						

Product data			
		Ref	kg/u
70	100	82002448	5,460
70	200	82002449	6,420
100	300	82002450	8,620
100	400	82002451	9,140
120	600	82002452	11,300

 Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

 Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic