

Nemaband 90° Outside Riser



Description

Metal accessory for creating an outside riser in the wiring installation with the Nemaband® ladder. It allows angles of descent and height changes to be made with great ease avoiding damage to the cable routing. Made from steel with GC Protection system.

Advantages

Cable tray connection using M8 screws or Nemaband® M8 joint kit

Inside and Outside risers available in 90°, 60°, 45°, 30° angles.

Reinforced profiles in C and Z formats that stiffen the construction of the cable ladder, to meet the demand in most markets.

CE certified in compliance with the low voltage directive 2014/35 / EU

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

Suitable for creating level or height changes in the Nemaband® ranges for routing, protecting and distributing cables in electrical installations in industrial applications and large spans in: Oil & Gas and Petrochemical Industry, Power Plants, Electric Power Plants, etc. Water Treatment, Mining and Cement Offshore Platforms, Ports, Maritime Applications. Industrial projects in aggressive environments.

Solutions



Main technical characteristics

 GC	 Class 8	 100, 150	 150, 300, 450, 600, 750, 900	 1	 Steel with surface coating	 20 J
 -50 / 150 °C	 A1 No combustible	ETIM 10 EC001535				

Product data

			Ref		kg/u
100	150	300	30	82002990	2,290
100	300	300	30	82002991	2,740
100	450	300	30	82002992	3,200
100	600	300	30	82002993	3,660
100	750	300	30	82002994	4,110
100	900	300	30	82002995	4,570
150	150	300	30	82002996	3,130
150	300	300	30	82002997	3,590
150	450	300	30	82002998	4,040
150	600	300	30	82002999	4,500
150	750	300	30	82003000	4,960
150	900	300	30	82003001	5,410
100	150	600	30	82003002	3,020
100	300	600	30	82003003	3,710
100	450	600	30	82003004	4,390
100	600	600	30	82003005	5,080
100	750	600	30	82003006	5,760
100	900	600	30	82003007	6,440
150	150	600	30	82003008	4,130
150	300	600	30	82003009	4,820
150	450	600	30	82003010	5,500
150	600	600	30	82003011	6,190
150	750	600	30	82003012	6,870
150	900	600	30	82003013	7,560
100	150	300	45	82003014	2,780
100	300	300	45	82003015	3,460
100	450	300	45	82003016	4,140
100	600	300	45	82003017	4,830
100	750	300	45	82003018	5,510
100	900	300	45	82003019	6,200
150	150	300	45	82003020	3,790
150	300	300	45	82003021	4,470
150	450	300	45	82003022	5,160
150	600	300	45	82003023	5,840
150	750	300	45	82003024	6,520

Nemaband 90° Outside Riser

				Ref	kg/u
150	900	300	45	82003025	7,210
100	150	600	45	82003026	3,540
100	300	600	45	82003027	4,220
100	450	600	45	82003028	4,910
100	600	600	45	82003029	5,590
100	750	600	45	82003030	6,280
100	900	600	45	82003031	6,960
150	150	600	45	82003032	4,950
150	300	600	45	82003033	5,630
150	450	600	45	82003034	6,320
150	600	600	45	82003035	7,000
150	750	600	45	82003036	7,690
150	900	600	45	82003037	8,370
100	150	300	60	82003038	3,040
100	300	300	60	82003039	3,720
100	450	300	60	82003040	4,400
100	600	300	60	82003041	5,090
100	750	300	60	82003042	5,770
100	900	300	60	82003043	6,460
150	150	300	60	82003044	4,220
150	300	300	60	82003045	4,900
150	450	300	60	82003046	5,590
150	600	300	60	82003047	6,270
150	750	300	60	82003048	6,950
150	900	300	60	82003049	7,640
100	150	600	60	82003050	4,050
100	300	600	60	82003051	4,740
100	450	600	60	82003052	5,420
100	600	600	60	82003053	6,110
100	750	600	60	82003054	6,790
100	900	600	60	82003055	7,470
150	150	600	60	82003056	5,770
150	300	600	60	82003057	6,450
150	450	600	60	82003058	7,130
150	600	600	60	82003059	7,820
150	750	600	60	82003060	8,500
150	900	600	60	82003061	9,190
100	150	300	90	82003062	3,570
100	300	300	90	82003063	0,000
100	450	300	90	82003064	4,930
100	600	300	90	82003065	5,620



Nemaband 90° Outside Riser

				Ref	kg/u
100	750	300	90	82003066	6,300
100	900	300	90	82003067	6,990
150	150	300	90	82003068	5,080
150	300	300	90	82003069	5,770
150	450	300	90	82003070	6,450
150	600	300	90	82003071	7,140
150	750	300	90	82003072	7,820
150	900	300	90	82003073	8,500
100	150	600	90	82003074	5,330
100	300	600	90	82003075	6,240
100	450	600	90	82003076	7,150
100	600	600	90	82003077	8,060
100	750	600	90	82003078	8,980
100	900	600	90	82003079	9,890
150	150	600	90	82003080	7,640
150	300	600	90	82003081	8,560
150	450	600	90	82003082	9,470
150	600	600	90	82003083	10,400
150	750	600	90	82003084	11,300
150	900	600	90	82003085	12,200

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Nemaband 90° Outside Riser

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

