

PQ Outside Riser PQU AL Outside Riser



Description

Metal accessory for creating an outside riser in the wiring installation with the Pemsaband® PQU AL tray. It allows ascents and height changes to be made with great ease, avoiding damage to the cable routing. Assembly using bolts. Made from Aluminium alloy 1050H24.

Advantages

Available in 30, 50 and 60 mm height and 100, 200, 300, 400, and 600 mm wide.

Its conical tip allows more contact with the element to which it is screwed.

CEPSA product approval. Designed according to ESP-2208-5 specification.

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Made of Aluminum alloy 1050H24. Excellent corrosion resistance and mechanical properties.

Applications

Suitable for fixing Rejiband® trays to supports for cable management in electrical and telecommunications installations, industrial installations, infrastructure and civil works and the service sector.

Solutions



Main technical characteristics									
 AL	 30, 60	 100, 200, 300, 400, 600	 200	 1	 Aluminum	 20 J	 -50 / 150 °C		
 A1 No combustible	ETIM 10 EC002400								

Product data			
		Ref	kg/u
30	100	82002358	0,547
30	200	82002359	0,888
30	300	82002360	1,230
30	400	82002361	1,570
30	600	82002362	2,250
60	100	82002363	0,806
60	200	82002364	1,150
60	300	82002365	1,490
60	400	82002366	1,830
60	600	82002367	2,510

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic