



45° PQ Bend



Description

Metal accessory for the creation of a 45° bend with the Pemsaband® PQU and PQW tray. Joins with nuts and bolts. Approved according to CEPSA and REPSOL specifications. Made of steel, with GC Protection System 85 microns thick.

Advantages

Compatible with Pemsaband® PQU and Pemsaband® PQW ranges.

Available for all heights 15, 30, 50, 60 and in widths from 100 to 600.

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Specially designed for the petrochemical sector, with CEPSA and REPSOL approvals.

GC protection system (standard UNE-EN ISO 1461), suitable for outdoor installations and in aggressive environments. Corrosion resistance class 8 according to IEC 61537.

Applications

Suitable for the creation of 45° bends in Pemsaband® PQU and PQW trays, for the Support, management and distribution of cables in Petrochemical, Oil & Gas, Offshore, Civil works and Infrastructures, as well as in tunnels and installation galleries.

Solutions



Main technical characteristics

 GC	 Class 8	 15, 30, 50, 60	 100, 150, 200, 300, 400, 500, 600	 100	45	 1
 Steel with surface coating	 20 J	 -50 / 150 °C	 A1 No combustible	ETIM 10 EC002400		

Product data

		Ref	kg/u
15	100	70213010	0,380
15	150	70213015	0,616
15	200	70213020	0,881
15	300	70213030	1,530
30	100	70213110	0,440
30	150	70213115	0,681
30	200	70213120	0,962
30	300	70213130	1,630
30	400	70213140	2,420
30	500	70213150	3,380
30	600	70213160	4,450
50	100	70213210	0,520
50	150	70213215	0,775
50	200	70213220	1,070
50	300	70213230	1,760
50	400	70213240	2,580
50	500	70213250	3,570
50	600	70213260	4,670
60	100	70213310	0,560
60	150	70213315	0,822
60	200	70213320	1,120
60	300	70213330	1,830
60	400	70213340	2,660
60	500	70213350	3,670
60	600	70213360	4,780

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint

45° PQ Bend

- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

