



Description

Advantages

Applications

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



45° bend Pemsaband Vulcan

Main technical characteristics

PG3, Pregalvanised, ZM High Resistance Alloy	12, 18, 25, 50	50, 75, 100, 150, 225, 300, 450, 600, 750, 900	1
Steel with surface coating	20 J	IP44	-50 / 150 °C
		A1 No combustible	ETIM 10

Product data

§	Ⓕ	Class	Ⓜ	Ⓜ	Ref	kg/u
PG	PG3, Pregalvanised	Class 3	12	50	82004756	0,140
PG	PG3, Pregalvanised	Class 3	12	75	82004757	0,197
PG	PG3, Pregalvanised	Class 3	12	100	82004758	0,252
PG	PG3, Pregalvanised	Class 3	12	150	82004759	0,377
PG	PG3, Pregalvanised	Class 3	12	225	82004760	0,591
PG	PG3, Pregalvanised	Class 3	18	300	82004761	1,276
PG	PG3, Pregalvanised	Class 3	25	50	82004762	0,191
PG	PG3, Pregalvanised	Class 3	25	75	82004763	0,253
PG	PG3, Pregalvanised	Class 3	25	100	82004764	0,310
PG	PG3, Pregalvanised	Class 3	25	150	82004765	0,440
PG	PG3, Pregalvanised	Class 3	25	225	82004766	0,661
PG	PG3, Pregalvanised	Class 3	25	300	82004767	1,369
PG	PG3, Pregalvanised	Class 3	25	450	82004768	2,250
PG	PG3, Pregalvanised	Class 3	25	600	82004769	3,309
PG	PG3, Pregalvanised	Class 3	50	50	82004770	0,283
PG	PG3, Pregalvanised	Class 3	50	75	82004771	0,349
PG	PG3, Pregalvanised	Class 3	50	100	82004772	0,409
PG	PG3, Pregalvanised	Class 3	50	150	82004773	0,545
PG	PG3, Pregalvanised	Class 3	50	225	82004774	1,164
PG	PG3, Pregalvanised	Class 3	50	300	82004775	1,557
PG	PG3, Pregalvanised	Class 3	50	450	82004776	2,467
PG	PG3, Pregalvanised	Class 3	50	600	82004777	3,556
PG	PG3, Pregalvanised	Class 3	50	750	82004778	7,929
PG	PG3, Pregalvanised	Class 3	50	900	82004779	10,316
PG	PG3, Pregalvanised	Class 3	25	750	82004780	7,458
PG	PG3, Pregalvanised	Class 3	25	900	82004781	9,797
AZ+	ZM High Resistance Alloy	Class 8	25	750	82004782	7,458
AZ+	ZM High Resistance Alloy	Class 8	25	900	82004783	9,797
AZ+	ZM High Resistance Alloy	Class 8	25	50	82004784	0,191
AZ+	ZM High Resistance Alloy	Class 8	25	75	82004785	0,253
AZ+	ZM High Resistance Alloy	Class 8	25	100	82004786	0,310
AZ+	ZM High Resistance Alloy	Class 8	25	150	82004787	0,440
AZ+	ZM High Resistance Alloy	Class 8	25	225	82004788	0,661
AZ+	ZM High Resistance Alloy	Class 8	25	300	82004789	1,369
AZ+	ZM High Resistance Alloy	Class 8	25	450	82004790	2,250



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Ⓢ	Ⓕ	EN 61537			Ref	kg/u
AZ+	ZM High Resistance Alloy	Class 8	25	600	82004791	3,309
AZ+	ZM High Resistance Alloy	Class 8	50	50	82004792	0,283
AZ+	ZM High Resistance Alloy	Class 8	50	75	82004793	0,349
AZ+	ZM High Resistance Alloy	Class 8	50	100	82004794	0,409
AZ+	ZM High Resistance Alloy	Class 8	50	150	82004795	0,545
AZ+	ZM High Resistance Alloy	Class 8	50	225	82004796	1,164
AZ+	ZM High Resistance Alloy	Class 8	50	300	82004797	1,557
AZ+	ZM High Resistance Alloy	Class 8	50	450	82004798	2,467
AZ+	ZM High Resistance Alloy	Class 8	50	600	82004799	3,556
AZ+	ZM High Resistance Alloy	Class 8	50	750	82004974	7,929
AZ+	ZM High Resistance Alloy	Class 8	50	900	82004975	10,316

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic