



Description
Advantages
Applications
Solutions



Main technical characteristics

PG3, Pregalvanised, ZM High Resistance Alloy	12, 18, 25, 50	50, 75, 100, 150, 225, 300, 450, 600, 750, 900	ETIM 10
Steel with surface coating	20 J	IP44	-50 / 150 °C
		A1 No combustible	

Product data

Ⓢ	ⓕ	Class EC 61537	Ⓜ	Ⓚ	Ref	kg/l
PG	PG3, Pregalvanised	Class 3	12	50	82004712	0,162
PG	PG3, Pregalvanised	Class 3	12	75	82004713	0,230
PG	PG3, Pregalvanised	Class 3	12	100	82004714	0,306
PG	PG3, Pregalvanised	Class 3	12	150	82004715	0,456
PG	PG3, Pregalvanised	Class 3	12	225	82004716	0,754
PG	PG3, Pregalvanised	Class 3	18	300	82004717	1,710
PG	PG3, Pregalvanised	Class 3	25	50	82004718	0,221
PG	PG3, Pregalvanised	Class 3	25	75	82004719	0,298
PG	PG3, Pregalvanised	Class 3	25	100	82004720	0,372
PG	PG3, Pregalvanised	Class 3	25	150	82004721	0,531
PG	PG3, Pregalvanised	Class 3	25	225	82004722	0,837
PG	PG3, Pregalvanised	Class 3	25	300	82004723	1,803
PG	PG3, Pregalvanised	Class 3	25	450	82004724	3,169
PG	PG3, Pregalvanised	Class 3	25	600	82004725	4,861
PG	PG3, Pregalvanised	Class 3	50	50	82004726	0,319
PG	PG3, Pregalvanised	Class 3	50	75	82004727	0,399
PG	PG3, Pregalvanised	Class 3	50	100	82004728	0,479
PG	PG3, Pregalvanised	Class 3	50	150	82004729	0,652
PG	PG3, Pregalvanised	Class 3	50	225	82004730	1,475
PG	PG3, Pregalvanised	Class 3	50	300	82004731	2,043
PG	PG3, Pregalvanised	Class 3	50	450	82004732	3,469
PG	PG3, Pregalvanised	Class 3	50	600	82004733	5,220
PG	PG3, Pregalvanised	Class 3	50	750	82004734	12,117
PG	PG3, Pregalvanised	Class 3	50	900	82004735	16,232
PG	PG3, Pregalvanised	Class 3	25	750	82004736	11,416
PG	PG3, Pregalvanised	Class 3	25	900	82004737	15,435
AZ+	ZM High Resistance Alloy	Class 8	25	750	82004738	11,416
AZ+	ZM High Resistance Alloy	Class 8	25	900	82004739	15,435
AZ+	ZM High Resistance Alloy	Class 8	25	50	82004740	0,221
AZ+	ZM High Resistance Alloy	Class 8	25	75	82004741	0,298
AZ+	ZM High Resistance Alloy	Class 8	25	100	82004742	0,372
AZ+	ZM High Resistance Alloy	Class 8	25	150	82004743	0,531
AZ+	ZM High Resistance Alloy	Class 8	25	225	82004744	0,837
AZ+	ZM High Resistance Alloy	Class 8	25	300	82004745	1,803
AZ+	ZM High Resistance Alloy	Class 8	25	450	82004746	3,169



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management. S.A."



Ⓢ	Ⓕ	EN 61537			Ref	kg/u
AZ+	ZM High Resistance Alloy	Class 8	25	600	82004747	4,861
AZ+	ZM High Resistance Alloy	Class 8	50	50	82004748	0,319
AZ+	ZM High Resistance Alloy	Class 8	50	75	82004749	0,399
AZ+	ZM High Resistance Alloy	Class 8	50	100	82004750	0,479
AZ+	ZM High Resistance Alloy	Class 8	50	150	82004751	0,652
AZ+	ZM High Resistance Alloy	Class 8	50	225	82004752	1,475
AZ+	ZM High Resistance Alloy	Class 8	50	300	82004753	2,043
AZ+	ZM High Resistance Alloy	Class 8	50	450	82004754	3,469
AZ+	ZM High Resistance Alloy	Class 8	50	600	82004755	5,220
AZ+	ZM High Resistance Alloy	Class 8	50	750	82004972	12,117
AZ+	ZM High Resistance Alloy	Class 8	50	900	82004973	16,232

Ⓢ Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic