





### Description

T-shape metal part for Pemsaband® and Inducanal® trays. Of 60 mm height, Width 600 mm, With INOX protection system, I316L finish. It enables the construction of a T-shaped junction at any point, although the trays may have different widths. Quick connection assembly using the Click system without couplers. Made of steel in various sizes and Protection Systems.

### Advantages

Side flanges have the same profile as the straight section of the trays thus forming a continual view of the installation.

It has pre-formed holes in the sides to allow for the connection of fittings and conduits for the exit of cables.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

The PG protection system is supplied flat for later assembly and provides savings on transportation and storage by reducing its volume.

Assembly by means of the quick-connect click system without the need for couplers. Patented Universal System that has holes compatible with the connection to other sheet metal tray.

### Applications

It is used to create a junction at any point between Pemsaband® One perforated and solid trays of different widths for the Support, management and distribution of Electrical and/or telecommunications cables in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

### Solutions



Product data

|                                       |                           |                                |                            |
|---------------------------------------|---------------------------|--------------------------------|----------------------------|
| ETIM 10                               | EC001006                  | u                              | 1                          |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) | 4,292                     | Material                       | Acero inoxidable AISI 316L |
| Protection System                     | INOX                      | Impact Strength (J)            | 20 J                       |
| Finish                                | Stainless Steel AISI 316L | IP                             | IP44                       |
| Resistance Class                      | Class 9D                  | Working temperature range (°C) | -50 / 150 °C               |
| Flange (mm)                           | 60                        | Fire resistance                | A1 No combustible          |
| Width (mm)                            | 600                       |                                |                            |
| R (mm)                                | 100                       |                                |                            |
| kg/u                                  | 0,808                     |                                |                            |

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

## Product applications





