



Description

Tee in self-extinguishing polyamide 6 for a branch in Pemsaflex® conduit. Protection rating IP54, IP67 with additional inner seal. The shape of the Pemsaflex® Tee is used to create an angled branch in the cable run, converting one line of conduits into two.

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Suitable for a tee joint of flexible conduits from the Pemsaflex® range. The two branches can be rotated so that the angle can be changed.

Click connection system that allows easy and fast coupling to the conduit.

Working temperature: -25°C to + 105°C. Degree of protection IP54 according to classification EN60529.

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions



Product data

ETIM 10	EC002922	Material	Polyamide 6
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		IP	IP54
Colour	Black RAL 9005	Working temperature range (°C)	-25 / 105 °C
DN	NW29	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
DN2	NW23		
kg/u	0,111		
u	10		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

