


Angle **tray** Fastener



Description

Fixing for the support of Rejiband® Angle wire mesh tray to a beam to ensure a perfect fit. Made of steel and with EZ or BC Protection System.

Advantages

Quick assembly, screw fastening.

Saves on time and installation costs.

High anti-corrosion properties.

For the the fixing of straight sections.

For the correct support of the angled tray on the beam it is necessary to use a fixing every 1 metre.

Applications

Used for the fixing of straight sections of Angle tray to a beam for the management of wiring in indoor installations with dry atmospheres and no contaminants.

Solutions



Main technical characteristics

ETIM 10
EC000474

Product data

Ⓢ	Class EC 61537	Ref	kg/u	Ⓜ	Ⓜ	Ⓜ	Ⓜ
EZ	Class 3	67010051	0,172	10	Steel with surface coating	-50 / 150 °C	A1 No combustible

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product applications

