


Variable Ceiling Rod Bracket



Description

Adjustable metal bracket for the ceiling mounting of Rejiband® wire mesh trays and Pemsaband® sheet trays with a M8 or M10 threaded rod. Easy orientation of the fixing of the necessary angle in electrical or telecommunications installations. Made of steel and GC Protection System.

Advantages

Connection with M8 or M10 threaded rod using hexagonal nuts.

Suitable for the support of all ranges of cable trays.

Suitable for sloping ceiling installations with confined spaces, thanks to its reduced dimensions.

CE conformity to directive 2014/35 / EU.

GC protection system (standard UNE-EN ISO 1461), suitable for outdoor installations and in aggressive environments. Corrosion resistance class 6.

Applications

Suitable for supporting medium loads of cable trays to the ceiling by means of a variable angled rod for electrical installations and / or of telecommunications in: Civil works, tunnels, car parks, public buildings, commercial centres, large infrastructures such as: Airports, underground, rail, tertiary sector, industrial naval, petrochemical, textile, chemical and food applications.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

ETIM 10

EC000896

Product data

		REF	kg/u					
GC	Class 8	67030061	0,139	1	Steel with surface coating	127	-50 / 150 °C	A1 No combustibile

 Protection System


- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

Variable Ceiling Rod Bracket

Product applications



Variable Ceiling Rod Bracket

