


Metatray perforated tray



Description

Perforated tray made of insulating material Grey RAL 7035 colour for the support, protection and conduction of cables. Maximum functionality and adaptation to different spaces and environments. Excellent performance in corrosive environments, weathering and exposure to UV radiation. Wide range of accessories with multiple applications. Tray with cover (insulating protective trunking) according to EN 50085. Complies with REACH and ROHS III directives. Free of dangerous substances.

Advantages

Insulating material, electrical safety and reduced maintenance costs.

Excellent performance in corrosive environments, weather and exposure to UV radiation.

The perforations in the longitudinal direction assist in the fixing and clamping of the cables.

Non-flame-propagating. Reaction to fire, V0 grade and M1 classification

Protection grade IP 2X and Impact Grade 20 J, 10 J 60x100 (EN 61537) and IK10 (EN50085)

Aenor N mark on product standards EN 61537 and EN 50085. CE compliance with directive 2014/35/EU.

Applications

Suitable for supporting, protecting and guiding cables in electrical and telecommunications installations in different sectors from wastewater treatment plants to the chemical and petrochemical industry, establishing itself as a highly corrosion-resistant solution that meets the most demanding standards. Its application is also ideal in other different sectors: service, telecommunications, electric mobility through vehicle charging stations etc.

Solutions



Main technical characteristics													
COLOUR	Grey RAL 7035		60, 100		100, 150, 200, 300, 400, 500, 600		3		IP23		-20 / 60 °C		GRADO UL94: V0
	Resistant acc. to UL568		ETIM 10 EC000047										


Product data						
		Ref	kg/u			mm²
60	100	82004160	0,973	24	10 J	4666
60	150	82004161	1,276	12	20 J	7183
60	200	82004162	1,573	12	20 J	9692
60	300	82004163	2,413	12	20 J	14689
60	400	82004164	3,436	6	20 J	19934
100	200	82004165	2,414	6	20 J	16611
100	300	82004166	3,188	6	20 J	25229
100	400	82004167	4,041	6	20 J	33825
100	500	82004168	4,960	6	20 J	42360
100	600	82004169	6,041	6	20 J	50917

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic


Load diagrams

Cargas de trabajo admisibles (CTA) y datos dimensionales / *Safety working loads (SWL) and dimensional data*
Charges de travail admissibles (CTA) et données dimensionnelles / *Cargas de trabalho admissíveis (CTA) e dados dimensionais*



Bandejas **metatray**® perforadas y ciegas / *Perforated and solid metatray*® cable trays
Chemins de câbles metatray® perforés et pleins / *Caminhos de cabos metatray*® perfurados e não perfurados

Secciones útiles mm² / *Useful cross sections mm²* / *Sections utiles mm²* / *Secções úteis mm²*


 x 	60x100	60x150	60x200	60x300	60x400	100x200	100x300	100x400	100x500	100x600
mm ²	4666	7183	9692	14869	19934	16611	25229	33825	42360	50917

Ensayos Carga de trabajo admisible (CTA) para bandejas (N/m) / *Safety working loads (SWL) tests for cable trays (N/m)* /
Essais de charge de travail admissible (CTA) pour les chemins de câbles (N/m) / *Ensaaios Carga de trabalho admissível (CTA) para*
caminhos de cabos (N/m)

		60x100	60x150	60x200	60x300	60x400	100x200	100x300	100x400	100x500	100x600
60°C	1 m	120	150	250	350	450	400	450	600	700	800
40°C	1,5 m										

Los ensayos CTA de las medidas de 300 a 600 han sido realizados con las uniones centrales refuerzo, referencias 82004223 y 82004224. / *The SWL tests from 300 to 600 were performed with the reinforced central joints, references 82004223 and 82004224.*

Condiciones del ensayo de carga de trabajo admisible para bandejas EN 61537 / *Safety working load test conditions for cable trays EN 61537* / *Conditions de l'essai de charge de travail admissible pour les chemins de câbles selon la norme EN 61537* / *Condições do ensaio de carga de trabalho admissível para caminhos de cabos EN 61537*

Temperatura / <i>Temperature</i> / <i>Température</i> / <i>Temperatura</i>	40°C	60°C
 Distancia entre soportes / <i>Support Span</i> / <i>Distance entre les supports</i> / <i>Distância entre suportes</i>	1,5 m	1 m
Flecha longitudinal / <i>Longitudinal deflection</i> / <i>Fèche longitudinale</i> / <i>Seta longitudinal</i>	Inferior al 1% de distancia entre soportes / <i>Less than 1% support span</i> / <i>Inférieure à 1 % de la distance entre les supports</i> / <i>Inferior a 1% de distância entre suportes</i>	
Flecha transversal / <i>Transverse deflection</i> / <i>Fèche transversale</i> / <i>Seta transversal</i>	Inferior al 5% del ancho de la bandeja / <i>Less than 5% of the cable tray width</i> / <i>Inférieure à 5 % de la largeur du chemin de câbles</i> / <i>Inferior a 5% da largura do caminho de cabos</i>	
Ubicación de uniones <i>Placement of joints</i> <i>Emplacement des éclisses</i> <i>Localização de uniões</i>		
Factor de seguridad sin alcanzar colapso <i>Increased safety coefficient</i> <i>Facteur de sécurité sans effondrement</i> <i>Fator de segurança sem alcançar colapso</i>	1,7 veces la carga de trabajo de seguridad declarada <i>1.7 times the declared safety working load</i> <i>1,7 fois la charge de travail sécurisée déclarée</i> <i>1,7 vezes a carga de trabalho de segurança declarada</i>	

Product applications



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Metatray perforated tray

