



**Flat Ring** ( Ref: 39090048 )

1/2



**Description**

Flat ring of NBR elastomer in blue colour, metric and PG thread for use with external threaded fittings and cable glands to provide an IP67 protection index to the joint. Available in various sizes.

**Advantages**

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in NBR elastomer in blue colour RAL 5024.

Protection index EN 60529: IP68.

**Applications**

Suitable for improving the tightness or the IP rating in the external thread of fittings for conduits or cable glands for the conduction or protection of wiring in general and industrial applications.

**Solutions**



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

**Flat Ring** ( Ref: 39090048 )

2/2

**Product data**

|                                              |               |                                       |                 |
|----------------------------------------------|---------------|---------------------------------------|-----------------|
| <b>ETIM 10</b>                               | EC001181      | <b>u</b>                              | 50              |
| <b>Huella de CO2. GWP A1-A3 (kg CO2 eq.)</b> |               | <b>Material</b>                       | NBR             |
| <b>Colour</b>                                | Blue RAL 5024 | <b>IP</b>                             | IP68            |
| <b>M/PG</b>                                  | PG48          | <b>Working temperature range (°C)</b> | -25 / 120 °C    |
| <b>Ø d2 (mm)</b>                             | 69            | <b>Fire resistance</b>                | Flame retardant |
| <b>L (mm)</b>                                | 2             |                                       |                 |
| <b>kg/u</b>                                  | 0,025         |                                       |                 |

**Protection System**

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

**Insulating materials**

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

