


Earth Continuity Connector



Description

Copper braided connector to provide electrical continuity in terminated sections of trays.

Advantages

Electrical continuity guaranteed according to standard IEC61537.

Suitable for bonding all ranges of trays.

Available in two sizes: 12 mm² and 16 mm².

Applications

Suitable for connection between continuous lengths of Rejiband® wire mesh trays, ensuring electrical continuity.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Reijtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics					
 LTN	 10	 Brass	 -50 / 150 °C	 A1 No combustible	ETIM 10 EC002935

Product data		
Size	Ref	kg/u
12	68000036	0,014
16	68000037	0,020

 Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass
 Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic