



Description

Advantages

Applications

Solutions

Main technical characteristics

 60, 100, 120	 100, 150, 200, 300, 400, 500, 600, 450	 1	 Steel with surface coating	 IP44	 -50 / 150 °C
 A1 No combustible	ETIM 10 EC002413				

Product data

§	Class IEC 61537			Réf	kg/u
PG	Class 3	60	100	71022010	0,127
PG	Class 3	60	150	71022015	0,181
PG	Class 3	60	200	71022020	0,254
PG	Class 3	60	300	71022030	0,372
PG	Class 3	60	400	71022040	0,470
PG	Class 3	60	500	71022050	0,585
PG	Class 3	60	600	71022060	0,693
PG	Class 3	100	100	71024010	0,178
PG	Class 3	100	150	71024015	0,244
PG	Class 3	100	200	71024020	0,322
PG	Class 3	100	300	71024030	0,460
PG	Class 3	100	400	71024040	0,595
PG	Class 3	100	450	71024045	0,669
PG	Class 3	100	500	71024050	0,735
PG	Class 3	100	600	71024060	0,869
PG	Class 3	120	100	71025010	0,203
PG	Class 3	120	150	71025015	0,276
PG	Class 3	120	200	71025020	0,360
PG	Class 3	120	300	71025030	0,510
PG	Class 3	120	400	71025040	0,659
PG	Class 3	120	450	71025045	0,738
PG	Class 3	120	500	71025050	0,811
PG	Class 3	120	600	71025060	0,957
GC	Class 5	60	100	71032010	0,137
GC	Class 5	60	150	71032015	0,194
GC	Class 5	60	200	71032020	0,273
GC	Class 5	60	300	71032030	0,411
GC	Class 5	60	400	71032040	0,506
GC	Class 5	60	450	71032045	0,570
GC	Class 5	60	500	71032050	0,628
GC	Class 5	60	600	71032060	0,746
GC	Class 5	100	100	71034010	0,191
GC	Class 5	100	150	71034015	0,263
GC	Class 5	100	200	71034020	0,346
GC	Class 5	100	300	71034030	0,494

§	Class	W	H	Ref	kg/u
GC	Class 5	100	400	71034040	0,640
GC	Class 5	100	450	71034045	0,719
GC	Class 5	100	500	71034050	0,791
GC	Class 5	100	600	71034060	0,935
GC	Class 5	120	100	71035010	0,218
GC	Class 5	120	150	71035015	0,296
GC	Class 5	120	200	71035020	0,387
GC	Class 5	120	300	71035030	0,548
GC	Class 5	120	400	71035040	0,708
GC	Class 5	120	450	71035045	0,793
GC	Class 5	120	500	71035050	0,872
GC	Class 5	120	600	71035060	1,030
AZ+	Class 8	60	100	82003806	0,127
AZ+	Class 8	60	150	82003807	0,181
AZ+	Class 8	60	200	82003808	0,254
AZ+	Class 8	60	300	82003809	0,372
AZ+	Class 8	60	400	82003810	0,470
AZ+	Class 8	60	500	82003811	0,585
AZ+	Class 8	60	600	82003812	0,693
AZ+	Class 8	100	100	82004307	0,178
AZ+	Class 8	100	200	82004308	0,322
AZ+	Class 8	100	300	82004309	0,460
AZ+	Class 8	100	400	82004310	0,595
AZ+	Class 8	100	500	82004311	0,735
AZ+	Class 8	100	600	82004312	0,869

§ Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene

Reducer PEMSAband

4/4

PA6 - Halogen Free Polyamide 6**PA12** - Halogen Free Polyamide 12**PU** - Polyurethane**PE** - Polyethylene**NBR** - NBR rubber**PET** - Thermoplastic Polyester**TPV** - Thermoplastic