

Universal Bracket



Description

Metal support for the installation of boxes, luminaires or other devices to the Megaband® ladder. It allows for the support of light loads on the sidewalls of Megaband® ladder heights 60-120. Made of steel and with GC Protection System.

Advantages

For mounting on tray use the Pemsaband M6 Connection Kit.

Quick and easy installation.

Thanks to its design it allows the placing of accessories in various positions.

Allows wall mounting of all types of trays of intermediate widths and not very high loads.

Available in protection systems: PG, pre-galvanized and GC, hot-dip galvanized

Applications

Suitable for the installation of boxes or other devices on the Pemsaband® and Inducanal® trays and for the support of light loads on the wall, in the Support, management and distribution of Electrical and/or telecommunications cables in public buildings, infrastructures and civil works, tertiary sector and industrial applications. Compatible with the range of Megaband® ladder for use as a device holder.

Solutions



Universal Bracket

Main technical characteristics

 10	 Steel with surface coating	 -50 / 150 °C	 A1 No combustible	ETIM 10 EC001004
---	--	--	---	---------------------

Product data

⑤	Class	Ref	kg/u
PG	Class 3	70420911	0,184
GC	Class 8	70430911	0,196

⑤ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

⑥ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

