



Description

Reinforced ladder for large elevated loads in heavy industry The Megaband® REP ladder is made up of alternating welded steel rungs 250mm high and a safety edge to protect and strengthen the ladder. Made from steel with GC Protection system.

Advantages

Wide variety of sizes and accessories to adapt to the demands of each electrical installation.

4mm side rails and 3mm rungs thickness.

Specially designed for the petrochemical sector, with REPSOL approvals, ED-P-11-02

In accordance with the IEC 61537 and CE standard with respect to directive 2014/35 / EU.

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

This ladder is especially suitable for electrical installations to support large loads in industrial, petrochemical, oil & gas, power plant, mining and cement plants.

Solutions



Main technical characteristics

 GC	 Class 8	 70, 100, 120	 100, 200, 300, 400, 600	 Steel with surface coating	 20 J	 4
 -50 / 150 °C	 A1 No combustible	ETIM 10 EC000854				

Product data

			REF	kg/u		mm²
70	100	3	82002368	7,780	3	4600
70	200	3	82002369	8,440	3	9200
100	300	3	82002370	11,100	3	22800
100	400	3	82002371	11,700	3	30400
120	600	3	82002372	14,300	3	57600
70	100	6	82002373	7,780	6	4600
70	200	6	82002374	8,440	6	9200
100	300	6	82002375	11,100	6	22800
100	400	6	82002376	11,700	6	30400
120	600	6	82002377	14,300	6	57600

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

Product applications



