




Description

Metal cable gland with improved diaphragm closure system with NBR seal and an IP68 protection rating (10 bar) according to EN 60529. Available in metric threads from M12 to M63 and in PG7 to PG48 threads for various cable diameters. Made of nickel-plated brass. For ATEX applications with explosive atmospheres.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

ATEX Classification: II 2G 1D.

Made of nickel-plated brass.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C. Protection index EN 60529: IP68 with 10 bar pressure for water immersion.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in ATEX classified installations with risk of fire or explosion, industrial, OEM equipment manufacturing, outdoor, industrial and marine applications.

Solutions



OFFSHORE, PORTS



Product data			
ETIM 10		EC000441	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		LTN	
Finish		Nickel-plated brass	
M/PG		M16	
G (mm)		6	
Cable diameter range		4 / 8	
Ø d1 (mm)		11	
L (mm)		27	
Torque wrench		17	
kg/u		0,020	
u		50	
Material		LATÓN NIQUELADO,NBR,POLIAMIDA 6	
IP		IP68	
Working temperature range (°C)		-15 / 90 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

