



Description
Metal cable gland with diaphragm closure system for flat cables, and a protection index of IP65 according to EN 60529, PG16 for cables 7x13 mm. Manufactured in ...
Advantages
Applications
Solutions

Product data			
ETIM 10	EC000441	Torque wrench	24
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		kg/u	0,039
Protection System	LTN	u	50
Finish	Nickel-plated brass	Material	LATÓN NIQUELADO,NBR,POLIAMIDA 6
Flange (mm)	7	IP	IP65
Width (mm)	13	Working temperature range (°C)	-25 / 90 °C
M/PG	PG16	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
G (mm)	6.5		
Ø d1 (mm)	18		
L (mm)	30.5		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic