



### Description

Cable gland with diaphragm closure system and multi hole plug for 16 cables, protection rating IP65 according to EN 60529, M32 for cables NW 3. Manufactured in in colour Grey RAL 7035.

### Advantages

### Applications

### Solutions



| Product data                          |  |                                              |  |
|---------------------------------------|--|----------------------------------------------|--|
| ETIM 10                               |  | EC000441                                     |  |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |  |                                              |  |
| Colour                                |  | Grey RAL 7035                                |  |
| DN                                    |  | NW 3                                         |  |
| M/PG                                  |  | M32                                          |  |
| G (mm)                                |  | 10                                           |  |
| Ø d1 (mm)                             |  | 30                                           |  |
| Holes                                 |  | 16                                           |  |
| L (mm)                                |  | 51                                           |  |
| Torque wrench                         |  | 42                                           |  |
| kg/u                                  |  | 0,047                                        |  |
| u                                     |  | 25                                           |  |
| Material                              |  | POLIAMIDA 6,TPV                              |  |
| IP                                    |  | IP65                                         |  |
| Working temperature range (°C)        |  | -25 / 60 °C                                  |  |
| Fire resistance                       |  | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |  |

| Protection System                 |
|-----------------------------------|
| CU - Copper electroplated         |
| PG - Pregalvanised                |
| EZ - Electrogalvanised            |
| BC - Electrogalvanised Bichromate |
| BK8 - High Resistance Coating     |
| GC - Hot Dip Galvanising          |
| INOX - Stainless Steel            |
| PT - Polyester Paint              |
| AL - Aluminum                     |
| LN - Brass or Nickel-plated brass |

| Insulating materials                      |
|-------------------------------------------|
| PC+ABS - Halogen Free Polycarbonate + ABS |
| PVC - Polyvinyl Chloride                  |
| PP - Halogen Free Polypropylene           |
| PA6 - Halogen Free Polyamide 6            |
| PA12 - Halogen Free Polyamide 12          |
| PU - Polyurethane                         |
| PE - Polyethylene                         |
| NBR - NBR rubber                          |
| PET - Thermoplastic Polyester             |
| TPV - Thermoplastic                       |