



Description

Cable gland with diaphragm closure system for flat cables, and protection rating IP65 according to EN 60529, M50 for cables 12x33 mm. Manufactured in in colour Grey RAL 7035.

Advantages

Applications

Solutions



Product data			
ETIM 10		EC000441	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Colour		Grey RAL 7035	
Flange (mm)		12	
Width (mm)		33	
M/PG		M50	
G (mm)		18	
Ø d1 (mm)		45	
L (mm)		71	
Torque wrench		60	
kg/u		0,112	
u		5	
Material		POLIAMIDA 6,TPV	
IP		IP65	
Working temperature range (°C)		-25 / 60 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic