

TCM EMC Nut



Description

Advantages

Applications

Solutions



Main technical characteristics

 LTN

 PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, PG42, PG48, M12, M16, M20, M25, M32, M40, M50, M63

 Nickel-plated brass

 -60 / 200 °C

 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

ETIM 10

EC000940

Product data					
			Ref	kg/u	
PG 7	3.3	15	40016007	0,002	100
PG 9	3.3	18	40016009	0,002	50
PG11	3.5	21	40016011	0,003	50
PG13	3.5	23	40016013	0,003	50
PG16	3.5	26	40016016	0,004	50
PG21	4	32	40016021	0,008	25
PG29	4.6	40	40016029	0,010	20
PG36	5.6	50	40016036	0,017	10
PG42	5.6	60	40016042	0,033	5
PG48	6.1	65	40016048	0,036	5
M12	3.3	15	40017120	0,003	100
M16	3.5	19	40017160	0,004	50
M20	3.5	24	40017200	0,005	50
M25	3.5	30	40017250	0,009	25
M32	4	36	40017320	0,011	20
M40	4.6	45	40017400	0,017	10
M50	5.6	55	40017500	0,028	5
M63	6.7	70	40017630	0,038	5

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

TCM EMC Nut

- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

