



Pemsaband RX. Reinforced Cable tray (

1/3

Ref: 76124600)



Description

Perforated and reinforced sheet steel tray of 60 and 100 mm height, in GC or PG Protection System with a safety edge. Of 100 mm height, Width 600 mm, With 1.5 mm thickness. The Pemsaband® RX tray, with a gauge of 1.5 mm, is suitable for supporting and routing electrical cables of high loads. There are a wide variety of sizes to choose from according to the needs of each installation.

Advantages

Wide variety of sizes, protection systems and accessories to adapt to the requirements of each electrical installation.

Profiled safety edge for cable protection. It also prevents possible cuts when handled by the installer.

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Sheet thickness of 1.5 mm gives greater strength and load capacity.

E90 fire resistance (90 minutes, 1000°C) according to DIN 4102-12.

Applications

Support, management and distribution of cables in Electrical and/or telecommunications installations in: Civil Works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Data Processing Centres, Infrastructures, Airports, Underground and Railway. Tertiary sector and industrial applications: Naval, Petrochemical, Textile, Chemical and Food. Indoor applications in the dry or in exterior atmospheres with wet environments according to the various protection systems.

Solutions



OFFSHORE, PORTS TUNNELS INFRASTRUCTURES FIRE RESISTANCE SOLUTION



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data

ETIM 10	EC000047	Material	Steel with surface coating
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	29,044	Impact Strength (J)	20 J
Protection System	PG	Thickness (mm)	1.5
Finish	PG3, Pregalvanised	Section (mm2)	58198
Resistance Class	Class 3	IP	IP23
Flange (mm)	100	Working temperature range (°C)	-50 / 150 °C
Width (mm)	600	Fire resistance	A1 No combustible
Length (m)	3		
kg/u	8,992		
u	6		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

Pemsaband. Cable Tray

10/10/2026

Pemsaband RX. Reinforced Cable tray (


3/3

Ref: 76124600)

Load diagrams

□ □ □

Product applications



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

