




## Description

Solid metal cable tray with a screwless snap-fit connect system, Available in heights of 35, 60, and 100 mm, with PG and AZ+ protection systems. New profile design and flat safety edge maximize contact with the cover. Of 100 mm height, Width 200 mm, With AZ+ protection system. The Pemsaband® Speed solid cable tray is designed for supporting and managing electrical and telecommunications cables in medium and light loads. Its easy assembly, thanks to a screwless, snap-fit quick-connect system, saves on material and labor costs.

## Advantages

Regulatory compliance: designed and developed in accordance with edition 3 of IEC 61537, Directive 2014/35/EU (CE marking) and UKCA marking, ensuring safety and reliability in electrical installations.

New profiled and flat safety edge design, created to offer maximum protection for your cables and reinforce the cable tray structure. With an 80% increase in the contact surface between the cable tray and the cover, it ensures optimal electrical continuity, meeting the standards of IEC 61357 Edition 3.

Innovative design with a renewed and distinctive aesthetic, our cable trays offer a modern and attractive look, in addition to meeting the highest quality and safety standards.

Wide variety of sizes: heights 35, 60 and 100 mm, and widths from 60 to 600 mm, PG and AZ+ protection systems, and a complete range of accessories from the Pemsaband® family that allows adaptation to the requirements of each electrical installation.

Revolutionary screwless snap-fit quick-connect system, easy to install in just one step, and requires no additional tools or accessories. This innovative solution streamlines your installation process, saving you money on both materials and labor. Say goodbye to hassles and save time with our efficient and practical connection system!

## Applications

A system designed for the routing, support, transport, and distribution of cables in electrical and/or telecommunications installations. It is applicable to, among others, the following areas: - Buildings, including public buildings, shopping centers, and Data Centers (DCs) . - Civil works and infrastructure, such as tunnels, parking garages, airports, and subway and railway lines. - The service and industrial sectors, being suitable for applications in the manufacturing, chemical, and food industries. The system is suitable for rapid installation indoors in controlled atmospheres, as well as in outdoor installations or humid environments, selecting the appropriate protection and finishing system in each case based on the environmental and service conditions.

## Solutions



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

|                                       |                          |                                |                            |
|---------------------------------------|--------------------------|--------------------------------|----------------------------|
| ETIM 10                               | EC000047                 | u                              | 6                          |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |                          | Material                       | Steel with surface coating |
| Protection System                     | AZ+                      | Impact Strength (J)            | 20 J                       |
| Finish                                | ZM High Resistance Alloy | Section (mm2)                  | 20000                      |
| Resistance Class                      | Class 8                  | IP                             | IP44                       |
| Flange (mm)                           | 100                      | Working temperature range (°C) | -50 / 150 °C               |
| Width (mm)                            | 200                      | Fire resistance                | A1 No combustible          |
| Length (m)                            | 3                        |                                |                            |
| kg/u                                  | 2,828                    |                                |                            |

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

### BK8 - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Reijtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."


## Load diagrams

### Ensayos de carga CTA instalaciones verticales en desarrollo horizontal


Valores obtenidos según la norma IEC 61537, edición 3, según ensayo horizontal multi vano recogido en el punto 10.5.1 de dicha norma, con un coeficiente de seguridad del 170% y sin alcanzar en ningún caso el colapso.

### Load Tests for SWL installed in vertical horizontal way


Values obtained in accordance with IEC 61537, edition 3, according to the horizontal tests of multiple spans listed in point 10.5.1 of this standard, with a safety factor of 170% and without collapse in any case.




**PG** 35




**AZ+** 35




**PG** 60




**AZ+** 60



**PG** 100



**AZ+** 100



Las cargas expresadas en la tabla reflejan las **cargas máximas de trabajo admisible (CTA)** y que corresponden a la capacidad máxima de llenado. En una instalación en vertical - horizontal, para cantidad máxima de cables a incluir en una bandeja depende del agrupamiento y las opciones de embridado y fijación de los cables para que la instalación sea segura.

The loads shown in the table reflect the **maximum allowable working loads (MWL)** and correspond to the maximum filling capacity. In a vertical-to-horizontal installation, the maximum number of cables to be included in a tray depends on how the cables are bunched and the tying and securing options used to ensure a safe installation.










### Ensayos de carga CTA instalaciones horizontales

Valores obtenidos según la norma IEC 61537, edición 3, según ensayo horizontal multi vano recogido en el punto 10.3.4 de dicha norma, con un coeficiente de seguridad del 170% y sin alcanzar en ningún caso el colapso.

### Load Tests for SWL installed in the horizontal way

Values obtained in accordance with IEC 61537, edition 3, according to the horizontal tests of multiple spans listed in point 10.3.4 of this standard, with a safety factor of 170% and without collapse in any case.




## Ensayos de carga CTA instalaciones verticales en desarrollo vertical

Valores obtenidos según la norma IEC 61537, edición 3, según ensayo vertical - vertical multi vano (V-V) recogido en el punto 10.6 de dicha norma, con un coeficiente de seguridad del 170% y sin alcanzar en ningún caso el colapso.

## SWL load tests for vertical installations in vertical development.

Values obtained in accordance with IEC 61537, edition 3, according to the vertical - vertical multi-span (V-V) tests listed in point 10.6 of this standard, with a safety factor of 170% and without reaching collapse in any case.

|     |     | PG       | AZ+      | CTA/SWL<br>V-V kg/m (1 m) |
|-----|-----|----------|----------|---------------------------|
| 35  | 60  | 82004471 | 82004509 | 35                        |
|     | 100 | 82004472 | 82004510 | 43                        |
|     | 150 | 82004473 | 82004511 | 50                        |
|     | 200 | 82004474 | 82004512 | 71                        |
|     | 300 | 82004475 | 82004513 | 70                        |
| 60  | 60  | 82004476 | 82004514 | 60                        |
|     | 100 | 82004477 | 82004515 | 66                        |
|     | 150 | 82004478 | 82004516 | 82                        |
|     | 200 | 82004479 | 82004517 | 87                        |
|     | 300 | 82004480 | 82004518 | 92                        |
|     | 400 | 82004481 | 82004519 | 102                       |
|     | 500 | 82004482 | 82004520 | 122                       |
|     | 600 | 82004483 | 82004521 | 143                       |
| 100 | 100 | 82004484 | 82004522 | 102                       |
|     | 200 | 82004485 | 82004523 | 107                       |
|     | 300 | 82004486 | 82004524 | 122                       |
|     | 400 | 82004487 | 82004525 | 133                       |
|     | 500 | 82004488 | 82004526 | 143                       |
|     | 600 | 82004489 | 82004527 | 153                       |



Las cargas expresadas en la tabla reflejan las **cargas máximas de trabajo admisible (CTA)** y que corresponden a la capacidad máxima de llenado. En una instalación en vertical - vertical, para cantidad máxima de cables a incluir en una bandeja depende del agrupamiento y las opciones de embreado y fijación de los cables para que la instalación sea segura.

The loads shown in the table represent the **maximum allowable working loads (SWL)** and correspond to the maximum filling capacity. In a vertical-to-vertical installation, the maximum number of cables to be accommodated in a cable tray depends on the cables are bunched and the tying and securing options used to ensure a safe installation.

## Product applications



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

