



### Description

Metal cover used as end closure for the range of Pemsaband® One trays ensuring product tightness and a professional finish. Of 60 mm height, Width 100 mm, With GC protection system, HDG finish. Quick connection assembly using the Click system without couplers. Made of steel in various sizes and Protection Systems.

### Advantages

Safer professional finish.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

Its unique design allows the closure of the various Pemsaband® One perforated trays.

Using this part in the end of the tray provides the closure of the assembly.

### Applications

It is used as the closing end of the system of Pemsaband® One perforated and solid trays to improve the sealing and protection of the installation. Applicable in the management of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

### Solutions



| Product data                          |                         |                                |                            |
|---------------------------------------|-------------------------|--------------------------------|----------------------------|
| ETIM 10                               | EC001574                | u                              | 1                          |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) | 0,356                   | Material                       | Steel with surface coating |
| Protection System                     | GC                      | IP                             | IP44                       |
| Finish                                | HDG, Hot Dip Galvanised | Working temperature range (°C) | -50 / 150 °C               |
| Resistance Class                      | Class 5                 | Fire resistance                | A1 No combustible          |
| Flange (mm)                           | 60                      |                                |                            |
| Width (mm)                            | 100                     |                                |                            |
| kg/u                                  | 0,137                   |                                |                            |

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

## Product applications











