



### Description

Solid metal cover designed to protect the straight sections of the Rejiband® wire mesh trays, Pemsaband® One, and Megaband® ladder. Width 100 mm, With INOX protection system, I304 finish. Snap fit mounting without the need of screws or fixings. It has an extended overlap at the end that improves the coupling and sealing of two straight sections of cover. Made of steel and available in various Protection Systems and sizes.

### Advantages

It has a locking clip at the ends and a hole for a screw connection to close the cover so that it can only be opened with a tool

Available in various protection systems: PG, GC, BK8, AZ+ and stainless steel AISI 304 and AISI 316L.

Optimum adjustment on the metal trays giving them a greater protection.

Snap fit installation without any fixings.

If the cover is combined with the sheet metal tray, Pemsaband® One, it becomes an IP2X protected channel for perforated version and IP4X for solid version

### Applications

Recommended for the protection of electrical and telecommunications wiring housed in Rejiband®, Pemsaband® and Megaband® trays in electrical and telecommunications installations in public buildings, infrastructure and civil works, industrial installation or tertiary sector.

### Solutions



## Product data

|                                              |                          |                                       |                          |
|----------------------------------------------|--------------------------|---------------------------------------|--------------------------|
| <b>ETIM 10</b>                               | EC002403                 | <b>u</b>                              | 24                       |
| <b>Huella de CO2. GWP A1-A3 (kg CO2 eq.)</b> | 2,864                    | <b>Material</b>                       | Stainless steel AISI 304 |
| <b>Protection System</b>                     | INOX                     | <b>IP</b>                             | IP44                     |
| <b>Finish</b>                                | Stainless Steel AISI 304 | <b>Working temperature range (°C)</b> | -50 / 150 °C             |
| <b>Resistance Class</b>                      | Class 9C                 | <b>Fire resistance</b>                | A1 No combustible        |
| <b>Width (mm)</b>                            | 100                      |                                       |                          |
| <b>Length (m)</b>                            | 3                        |                                       |                          |
| <b>kg/u</b>                                  | 0,539                    |                                       |                          |

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

## Product applications





























