



Description

Advantages

Applications

Solutions



RENEWABLE ENERGIES



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics					
 PG3, Pregalvanised, HDG, Hot Dip Galvanised	 180, 350	 10	 Steel with surface coating	 100	 -50 / 150 °C
 A1 No combustible	ETIM 10 EC000022				

Product data					
				Ref	kg/u
PG	PG3, Pregalvanised	Class 3	180	67030539	0,217
PG	PG3, Pregalvanised	Class 3	350	67030540	0,337
GC	HDG, Hot Dip Galvanised	Class 6	180	67030541	0,224
GC	HDG, Hot Dip Galvanised	Class 6	350	67030542	0,348

 Protection System	
CU - Copper electroplated	
PG - Pregalvanised	
EZ - Electrogalvanised	
BC - Electrogalvanised Bichromate	
BK8 - High Resistance Coating	
GC - Hot Dip Galvanising	
INOX - Stainless Steel	
PT - Polyester Paint	
AL - Aluminum	
LN - Brass or Nickel-plated brass	

 Insulating materials	
PC+ABS - Halogen Free Polycarbonate + ABS	
PVC - Polyvinyl Chloride	
PP - Halogen Free Polypropylene	
PA6 - Halogen Free Polyamide 6	
PA12 - Halogen Free Polyamide 12	
PU - Polyurethane	
PE - Polyethylene	
NBR - NBR rubber	
PET - Thermoplastic Polyester	
TPV - Thermoplastic	