



Description

Advantages

Applications

Solutions



| Product data                          |  |                                |  |
|---------------------------------------|--|--------------------------------|--|
| ETIM 10                               |  | Material                       |  |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |  | Steel with surface coating     |  |
| Protection System                     |  | IP                             |  |
| Finish                                |  | Working temperature range (°C) |  |
| Resistance Class                      |  | Fire resistance                |  |
| Width (mm)                            |  |                                |  |
| Length (m)                            |  |                                |  |

| Protection System                 |
|-----------------------------------|
| CU - Copper electroplated         |
| PG - Pregalvanised                |
| EZ - Electrogalvanised            |
| BC - Electrogalvanised Bichromate |
| BK8 - High Resistance Coating     |
| GC - Hot Dip Galvanising          |
| INOX - Stainless Steel            |
| PT - Polyester Paint              |
| AL - Aluminum                     |
| LN - Brass or Nickel-plated brass |

| Insulating materials                      |
|-------------------------------------------|
| PC+ABS - Halogen Free Polycarbonate + ABS |
| PVC - Polyvinyl Chloride                  |
| PP - Halogen Free Polypropylene           |
| PA6 - Halogen Free Polyamide 6            |
| PA12 - Halogen Free Polyamide 12          |
| PU - Polyurethane                         |
| PE - Polyethylene                         |
| NBR - NBR rubber                          |
| PET - Thermoplastic Polyester             |
| TPV - Thermoplastic                       |