

7035 P Connector



Description

Basic straight halogen-free self-extinguishing polyamide 6 fitting for connecting flexible and spiral plastic conduits. Protection index IP65. Available in metric and PG threads for various conduit sizes. Body and nut in grey (RAL 7035).

Advantages

High aesthetic component. RAL 7035 grey same as the other conduits or electrical materials. Also available in dark grey RAL 7001.

Protection index EN 60529: IP65.

Working temperature: -25°C to + 105°C.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Applications

Suitable for the connection of TFA, TM-PVC and Ecoflex® flexible conduits, in the conduction of electrical cables for building, tertiary and industrial applications.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics							
Colour Grey RAL 7035		DN NW 9, NW11, NW13, NW16, NW21, NW29, NW36, NW48			M16, M20, M25, M32, M40, M50, M63		Polyamide 6
IP44	-25 / 105 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA			ETIM 10 EC001178		

Product data							
DN				L _{mm}	Ref	kg/u	
NW 9	M16	7.1	11	29.6	81000120	0,004	100
NW11	M20	7.7	15	33.2	81000121	0,006	50
NW13	M20	7.7	15	34.2	81000122	0,006	50
NW16	M25	8.1	20	37.1	81000123	0,009	25
NW21	M32	9	26	43	81000124	0,014	25
NW29	M40	10	33	51	81000125	0,022	10
NW36	M50	10	43	55.5	81000126	0,029	8
NW48	M63	11	55	62	81000127	0,046	5

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic