


P Connector



Description

Basic straight connector made of self-extinguishing polyamide 6 for the installation of flexible and spiral plastic conduits. IP44 protection index. Available in metric and PG thread various sizes of conduit, in GREY RAL 7001.

Advantages

Suitable for coupling TFA helicoidal flexible conduit.

Protection index EN 60529: IP65.

Working temperature: -25°C to + 105°C.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Applications

Suitable for the connection of TFA, TM-PVC and Ecoflex® flexible conduits, in the conduction of electrical cables for building, tertiary and industrial applications.

Solutions



Main technical characteristics

Colour	Grey RAL 7001	DN	NW 7, NW 9, NW11, NW13, NW16, NW21, NW29, NW36, NW48	
	PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, PG48, M16, M20, M25, M32, M40, M50, M63		Polyamide 6	IP44, IP65
		ETIM 10		
	-25 / 105 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	EC001178	

Product data

DN				L _{mm}	Ref	kg/ú		IP
NW 7	PG 7	9.1	8.1	27.2	30010007	0,003	100	IP44
NW 9	PG 9	9.1	10.6	28.2	30010009	0,004	100	IP44
NW11	PG11	9.7	14.1	31.9	30010011	0,005	50	IP44
NW13	PG13	10.2	15.7	33.4	30010013	0,006	50	IP65
NW16	PG16	10.6	17.2	34.2	30010016	0,008	25	IP65
NW21	PG21	12	21.8	40	30010021	0,012	25	IP65
NW29	PG29	13	26	47.5	30010029	0,021	10	IP65
NW36	PG36	13.5	37	51.5	30010036	0,027	8	IP65
NW48	PG48	16	59.3	59.3	30010048	0,043	5	IP65
NW 9	M16	9.1	11	28.2	30011160	0,004	100	IP65
NW11	M20	9.7	15	31.9	30011200	0,006	50	IP65
NW13	M20	10.2	15	33.4	30011201	0,006	50	IP65
NW16	M25	10.6	20	34.2	30011250	0,009	25	IP65
NW21	M32	12	26	40	30011320	0,014	25	IP65
NW29	M40	13	28.3	54	30011400	0,022	10	IP65
NW36	M50	13.5	36.6	59	30011500	0,029	8	IP65
NW48	M63	15	50	66	30011630	0,046	5	IP65

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene

P Connector

- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

