


PA6 RA 90° Connector



Description

Connector of 90° with external thread in The PA6 connector is suitable for the installation of Pemsaflex®, LG-PA, ST-PA, RB-PA and RB-PU flexible conduits. Self-extinguishing and

Advantages

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Click connection system that allows easy and fast coupling to the conduit.

Working temperature: -40°C to + 120°C.

Protection index EN 60529: IP54.

CE certified in compliance with the low voltage directive 2014/35 / EU

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions



Main technical characteristics										
COLOUR Grey RAL 7031, Black RAL 9005			DN NW 7, NW10, NW12, NW14, NW17, NW23			PG PG 7, PG 9, PG11, PG13, PG16, PG21, M12, M16, M20, M25				
90	 Polyamide 6	 IP54	 -40 / 120 °C	 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA				ETIM 10 EC001176		

COLOUR	DN					Lmm	Amm	Ref	kg/u	
Grey RAL 7031	NW 7	PG 7	11	8.2	18.7	36.3	36.3	31043007	0,007	75
Grey RAL 7031	NW10	PG 9	11	10.3	21.7	37.3	43.8	31043109	0,009	50
Grey RAL 7031	NW12	PG11	11	13.3	26	41	43.8	31043211	0,014	50
Grey RAL 7031	NW14	PG13	11	15.3	28	44	46	31043313	0,019	50
Grey RAL 7031	NW17	PG16	13	16.6	32	51.5	51	31043416	0,022	40
Grey RAL 7031	NW23	PG21	16	22.4	39.5	61.2	64.3	31043521	0,036	25
Grey RAL 7031	NW 7	M12	11	8.2	18.7	36.3	35.7	31044012	0,008	75
Grey RAL 7031	NW10	M16	11	10.8	21.7	37.3	38.5	31044116	0,010	50
Grey RAL 7031	NW12	M16	11	10.9	26	41	43.8	31044216	0,014	50
Grey RAL 7031	NW14	M20	11	14.7	28	44	46	31044320	0,013	50
Grey RAL 7031	NW17	M20	13	15.2	32	51.5	51	31044420	0,015	40
Grey RAL 7031	NW23	M25	16	18.7	39.5	61.2	64.3	31044525	0,038	25
Black RAL 9005	NW 7	PG 7	11	8.2	18.7	36.3	35.7	32043007	0,008	75
Black RAL 9005	NW10	PG 9	11	10.3	21.7	37.3	38.5	32043109	0,010	50
Black RAL 9005	NW12	PG11	11	13.3	26	41	43.8	32043211	0,014	50
Black RAL 9005	NW14	PG13	11	15.3	28	44	46	32043313	0,018	50
Black RAL 9005	NW17	PG16	13	16.6	32	51.5	51	32043416	0,022	40
Black RAL 9005	NW23	PG21	16	22.4	39.5	61.2	64.3	32043521	0,036	25
Black RAL 9005	NW 7	M12	11	8.2	18.7	36.3	35.7	32044012	0,007	75
Black RAL 9005	NW10	M16	11	10.8	21.7	37.3	38.5	32044116	0,009	50
Black RAL 9005	NW12	M16	11	10.9	26	41	43.8	32044216	0,014	50
Black RAL 9005	NW14	M20	11	14.7	28	44	46	32044320	0,015	50
Black RAL 9005	NW17	M20	13	15.2	32	51.5	51	32044420	0,015	40
Black RAL 9005	NW23	M25	16	18.7	39.5	61.2	64.3	32044525	0,038	25

 Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum

PA6 RA 90° Connector

3/3

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

