



Female Straight Connector

1/2



Description

Basic straight connector made of self-extinguishing polyamide 6 with internal thread in RAL 7011 gray or black RAL 9005, metric and PG thread, halogen-free, flame retardant, IP54 or IP67 protection index with additional inner seal. The internal connection of the conduit is suitable for the installation of Pemsaflex® flexible conduits LG-PA, ST-PA, RF-PA, RB-PA and RB-PU.

Advantages

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Click connection system that allows easy and fast coupling to the conduit.

It allows the connection, with another straight connection of external thread, for the joining of sections of conduits.

Working temperature: -25°C to + 105°C. Degree of protection IP54 according to classification EN60529.

UL and CSA certification. CE conformance with the 2014/35 directive and the IEC 61386 standard. Halogen-free according to EN 50267-2-1 standard. In accordance with standard EN 60204-1 (machine safety).

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics

Colour Grey RAL 7011	DN NW10, NW12, NW17, NW23, NW29	 PG 9, PG11, PG13, PG16, PG21, PG29	 Polyamide 6	 IP54
 -25 / 105 °C	 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM 10 EC001176		

Product data

DN							Ref	kg/u	
NW10	PG 9	12	11	21.7	35	19	31020109	0,004	50
NW12	PG11	13	13.4	24.8	37	22	31020211	0,005	50
NW17	PG13	13.5	17.2	28.5	39	24	31020413	0,009	50
NW17	PG16	13	17.3	33.2	39	30	31020416	0,008	50
NW23	PG21	14.5	21.7	36	52	32	31020521	0,017	30
NW29	PG29	18.5	30	47.5	57	42	31020629	0,024	30

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic