




Description

Straight connector in self-extinguishing polyamide 6 in grey RAL 7011 or black RAL 9005 with metric and PG metal thread, halogen-free, flame retardant, IP54 or IP67 protection rating with additional inner seal. The REP connector is suitable for the installation of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU flexible conduits.

Advantages

UL, CSA and DNV certification. CE conformance with the 2014/35 directive and the IEC 61386 standard. Halogen-free according to EN 50267-2-1 standard. In accordance with standard EN 60204-1 (machine safety).

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Protection index EN 60529: IP54 and IP67 with internal seal.

Click connection system that allows easy and fast coupling to the conduit.

Working temperature: -25°C to + 105°C.

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Product data			
ETIM 10		EC001176	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Colour		Grey RAL 7011	
DN		NW48	
M/PG		M50	
G (mm)		14	
Ø d1 (mm)		44.2	
Ø d2 (mm)		65.5	
L (mm)		62	
Torque wrench		60	
kg/u		0,048	
u		10	
Material		Polyamide 6	
IP		IP54	
Working temperature range (°C)		-25 / 105 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic