

RGM Double Connector (Ref: 82002570)



Description

Double swivel body metal fitting with nickel-plated brass metal inner bushes for connecting flexible conduits type TM, Ecoflex®, TFA and TM-PVC. Self-extinguishing polyamide 6 insulating outer body. IP65 protection rating. Available in grey (RAL 7035).

Advantages

It has an independent rotating body for both sides that allow the connection of the fitting to the conduit for later connection to the box.

It has a metal body and inner sleeve, thus facilitating connection with the metal interior of TM-PVC, Ecoflex and TM conduits, maintaining the electrical continuity of the system.

Double body that allows the connection of flexible conduits with a metal body and a plastic cover.

CE conformity in accordance to the low voltage directive 2014 /35 /UE and the international and harmonized product standard IEC 61537

Applications

Suitable for connecting TM, TM-PVC and Ecoflex® flexible metal conduits for electrical cable routing for building, service and industrial applications.

Solutions



Product data

ETIM 10	EC001178	kg/u	0,040
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	25
Protection System	LTN	Material	LATÓN NIQUELADO,POLIAMIDA 6
Finish	Nickel-plated brass	IP	IP65
Colour	Grey RAL 7001	Working temperature range (°C)	-25 / 105 °C
DN	NW13	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Ø d1 (mm)	14.3		
L (mm)	62		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product applications

□ □



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."