

RMH Female Connector (Ref: 37041500)

1/2

**Description**

Nickel-plated brass connector with internal thread and polyethylene inner sleeve for the assembly of TM, Ecoflex®, TM-PVC conduits. IP54 protection index. Available in various sizes and in metric threads.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

It has an internal female thread to allow the connection of RM external threads for joining lengths of flexible conduits.

Made of nickel-plated brass with a polypropylene inner sleeve.

Protection index EN 60529: IP54.

Working temperature: -25°C to + 90°C.

Applications

Suitable for the connection of TM, TM-PVC and Ecoflex® metallic flexible conduits, in the management of electrical cables for building, tertiary and industrial applications.

Solutions

Product data			
ETIM 10		EC001180	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		LTN	
Finish		Nickel-plated brass	
DN		NW36	
M/PG		M50	
G (mm)		10	
Ø d1 (mm)		34.8	
L (mm)		40	
Torque wrench		56	
kg/u		0,179	
u		10	
Material		LATÓN NIQUELADO,POLIPROPILENO	
IP		IP54	
Working temperature range (°C)		-25 / 90 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic