

Right Reducer Pemsaband Vulcan (Ref: 82005108)



Description

Advantages

Applications

Solutions



Product data	
ETIM 10	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Protection System	AZ+
Finish	ZM High Resistance Alloy
Resistance Class	Class 8
Flange (mm)	25
Width (mm)	450
Reduce to:	225

Material	Steel with surface coating
Impact Strength (J)	20 J
IP	IP44
Working temperature range (°C)	-50 / 150 °C
Fire resistance	A1 No combustible

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic