

**Right Reducer Pemsaband Vulcan** ( Ref: 82005127 )



Description

Advantages

Applications

Solutions



Product data

|                                       |                          |                                |                            |
|---------------------------------------|--------------------------|--------------------------------|----------------------------|
| ETIM 10                               |                          | Material                       | Steel with surface coating |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |                          | Impact Strength (J)            | 20 J                       |
| Protection System                     | AZ+                      | IP                             | IP44                       |
| Finish                                | ZM High Resistance Alloy | Working temperature range (°C) | -50 / 150 °C               |
| Resistance Class                      | Class 8                  | Fire resistance                | A1 No combustible          |
| Flange (mm)                           | 50                       |                                |                            |
| Width (mm)                            | 600                      |                                |                            |
| Reduce to:                            | 300                      |                                |                            |

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

