

Floor Foot



Description

Rejiband® accessory intended for the support of the Rejiband® wire mesh tray in installations on technical floors with a height of 40 mm. Press fit thanks to the Click system that allows a quick installation on Rejiband®. Made of red polystyrene.

Advantages

Installation in raised floors.

It allows for raising the height from 40 mm up to 73 mm by stacking a maximum of two supports.

Fast mount Click system.

It can be fixed with adhesive (ref. 68000066) or screwed to the floor.

High safety material, flammability V0 according to UL94 for black references.

Applications

Suitable for the installation of trays in raised floors and used for the management of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

Solutions



RENEWABLE ENERGIES



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics

Colour	Red RAL 3000, Black RAL 9005	 100	 Plastic	 40	 -15 / 90 °C	ETIM 10 EC000022
--------	------------------------------	---	---	--	---	---------------------

Product data

COLOUR	REF	kg/u	
Red RAL 3000	68000060	0,026	NO PROPAGADOR DE LA LLAMA,GRADO UL94: V2
Black RAL 9005	68000160	0,022	NO PROPAGADOR DE LA LLAMA,GRADO UL94: V0

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

