



Threaded Rod



Description

Metal threaded rod in various Protection Systems and different diameters for supporting or fixing components in roof mounted electrical installations with cable trays.

Advantages

Complete range of threaded rods in M6, M8 and M10.

E90 fire resistance (90 minutes, 1000°C) according to DIN 4102-12.

Available in different protection systems: EZ, BK8, GC, and stainless steel AISI 316.

Applications

Suitable for the installation of trays supported from the ceiling and used for the management of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

Solutions



FOOD INDUSTRY



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

 M 6, M 8, M10

 -50 / 150 °C

ETIM 10
EC000028

Product data

Ⓢ	Class	Ⓜ	L _{mm}	Ref	kg/u	Ⓜ	Ⓜ	IF	Ⓢ
EZ	Class 3	M 6	500	67010140	0,120	50	Steel with surface coating	195	A1 No combustible
EZ	Class 3	M 6	1000	67010141	0,240	50	Steel with surface coating	195	A1 No combustible
GC	Class 8	M 8	1000	67030045	0,320	50	Steel with surface coating	400	E90 (90 min. 1000°C)
INOX	Class 9D	M 8	500	67060044	0,160	50	Acero inoxidable AISI 316L	400	E90 (90 min. 1000°C)
INOX	Class 9D	M 8	1000	67060045	0,320	50	Acero inoxidable AISI 316L	400	E90 (90 min. 1000°C)
INOX	Class 9D	M 6	1000	67060141	0,240	50	Acero inoxidable AISI 316L	195	A1 No combustible
INOX	Class 9D	M10	1000	67060145	0,490	25	Acero inoxidable AISI 316L	500	E90 (90 min. 1000°C)
BK8	Class 8	M 8	1000	67080045	0,320	50	Steel with surface coating	400	E90 (90 min. 1000°C)
EZ	Class 3	M 8	500	81000440	0,160	50	Steel with surface coating	400	E90 (90 min. 1000°C)
EZ	Class 3	M 8	1000	81000441	0,320	50	Steel with surface coating	400	E90 (90 min. 1000°C)
EZ	Class 3	M10	1000	81000442	0,490	50	Steel with surface coating	500	E90 (90 min. 1000°C)

Ⓢ Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic


Threaded Rod

3/4

Load diagrams

□

Product applications



Threaded Rod

