



Threaded Rod (Ref: 67010141)

1/8



Description

M 6, M 6, M 6x1000 mm, With EZ protection system, EZ3 finish

Advantages

Applications

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data

ETIM 10	EC000028	u	50
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Material	Steel with surface coating
Protection System	EZ	F (kg)	195
Resistance Class	Class 3	Working temperature range (°C)	-50 / 150 °C
M/PG	M 6	Fire resistance	A1 No combustible
L (mm)	1000		
kg/u	0,240		

🔒 Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

🏠 Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene


NBR - NBR rubber


PET - Thermoplastic Polyester

TPV - Thermoplastic



Load diagrams

↓CTA↓ (kg)		kg
una varilla / one rod / uma varão		
	100-300	160

↓CTA↓ (kg)		kg
una varilla / one rod / uma varão		
	100-300	160

Product applications



