


RLH750 Halogen Free Conduit (Ref: 13006120

1/2



Description

RLH rigid pipe for the protection of electrical cables in building applications. Manufactured in halogen-free thermoplastic material (PC + ABS) with a protection rating of IP44, compression strength of 750 N and impact resistance of 6 J. Available in grey (RAL 7035), in a wide variety of sizes.

Advantages

- High security, halogen free material UNE/EN 60754-2 y UNE/EN 60754-1. Reduced smoke opacity and toxicity in the event of a fire. Flame retardant.
- CE conformity with directive 2014/35 and standard EN IEC 61386-21.
- Quick assembly via plug-in connection between conduits and fittings.
- Very good performance against impact and compression.
- It is produced in 3 m lengths for greater convenience of transport and handling.

Applications

Suitable for the protection of electrical cables in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions



SERVICE AND RETAIL



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RLH750 Halogen Free Conduit (Ref: 13006120

2/2

Product data

ETIM 10	EC001174	Cod. IEC.61386	3432
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0	Compression strength (N)	750 N
Colour	Grey RAL 7035	Impact Strength (J)	6 J
DN	NW20	IP	IP44
Ø d1 (mm)	17.2	Working temperature range (°C)	-15 / 90 °C
Ø d2 (mm)	20	Fire resistance	Flame retardant
kg/u	0,098		
u	57		
Material	Polycarbonate + ABS		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic