

RLH Coupler Kit IP65



Description

Coupler kit for connecting rigid halogen-free RLH or rigid RPVC conduits. Made of halogen-free thermoplastic (PC+ABS) with an IP65 protection rating. Available in light grey (RAL 7035).

Advantages

High security, halogen free material UNE/EN 60754-2 y UNE/EN 60754-1. Reduced smoke opacity and toxicity in the event of a fire. Flame retardant.

Quick assembly via plug-in connection between conduits and fittings.

High level of tightness and IP65 protection.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Applications

Suitable for joining rigid halogen-free and PVC conduits in buildings, service and industrial applications with high safety requirements especially public places.

Solutions



Main technical characteristics

Colour	Grey RAL 7035	DN	NW16, NW20, NW25, NW32, NW40, NW50, NW63		 Polycarbonate + ABS	 IP65	 -15 / 90 °C	
	 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA		ETIM 10 EC000939					

Product data

DN	L _{mm}	Ref	kg/u	
NW16	79.8	82003210	0,016	5
NW20	87.8	82003211	0,020	5
NW25	97.8	82003212	0,026	5
NW32	107.8	82003213	0,034	3
NW40	111.8	82003214	0,043	3
NW50	131.8	82003215	0,060	2
NW63	147.8	82003216	0,080	2

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

RLH Coupler Kit IP65

Product applications

