

## RLH fFemale Coupler IP65



### Description

Fitting with female internal thread for coupling fittings with external thread in the connection of rigid halogen-free RLH or rigid RPVC conduits with flexible TFA and TM-PVC conduits. Made of halogen-free thermoplastic (PC+ABS) with an IP65 protection rating. Available in light grey (RAL 7035).

### Advantages

For connection of rigid conduits and flexible conduits.

Quick assembly via plug-in connection for rigid conduits and inside threaded on the other side for flexible conduits

High level of tightness and IP65 protection.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

### Applications

Suitable for halogen-free and PVC rigid and flexible conduits in buildings, service and industrial applications with high safety requirements especially public places.

### Solutions



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

## RLH fFemale Coupler IP65

### Main technical characteristics

|                       |                                             |                                     |                                                 |
|-----------------------|---------------------------------------------|-------------------------------------|-------------------------------------------------|
| Colour Grey RAL 7035  | DN NW16, NW20, NW25, NW32, NW40, NW50, NW63 | ⌘ M16, M20, M25, M32, M40, M50, M63 | ⌘ 15                                            |
| Ⓜ Polycarbonate + ABS | Ⓜ IP54                                      | ⚠ -15 / 90 °C                       | ⚠ LIBRE DE HALÓGENOS, NO PROPAGADOR DE LA LLAMA |
|                       |                                             |                                     | ETIM 10 EC000939                                |

### Product data

| DN   | ⌘   | L <sub>mm</sub> | Ref      | kg/u  | Ⓜ  |
|------|-----|-----------------|----------|-------|----|
| NW16 | M16 | 34.5            | 81000070 | 0,005 | 20 |
| NW20 | M20 | 38.5            | 81000071 | 0,007 | 20 |
| NW25 | M25 | 43.5            | 81000072 | 0,009 | 20 |
| NW32 | M32 | 48.5            | 81000073 | 0,012 | 10 |
| NW40 | M40 | 50.5            | 81000074 | 0,016 | 10 |
| NW50 | M50 | 60.5            | 81000075 | 0,022 | 5  |
| NW63 | M63 | 68.5            | 81000076 | 0,030 | 5  |

### Ⓜ Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

### Ⓜ Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

