

RPVC 90° Bend



Description

90° PVC bend in grey (RAL 7035) with an IP44 index of protection for RPVC rigid conduits. Accessory is used for the assembly of PVC conduits with a push fit connection to the conduit, creating an angle of 90°. Opening for access to cables.

Advantages

For connection of rigid RPVC conduits.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection for conduits and accessories. It allows opening to access and manipulate the cables.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of PVC, not flame retardant.

Applications

Suitable for rigid PVC conduits in building, tertiary and industrial applications.

Solutions



Colour Grey RAL 7035	DN NW16, NW20, NW25, NW32	PVC	IP44	-5 / 60 °C	Flame retardant	ETIM 10 EC000936
---	---	---	--	--	---	---------------------

DN	吋	L _{mm}	R _{ef}	kg/u	個
NW16	16.5	42	55073016	0,007	25
NW20	20.5	50	55073020	0,010	25
NW25	25.5	60	55073025	0,015	25
NW32	30.5	72	55073032	0,023	15

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

